



**Dubai**

Ready-Mix Concrete  
CEMEX TOPMIX LLC  
PO Box 37900, Al-Quoz  
Industrial Area 3, Dubai, UAE  
Tel : +971 4 347 0427/477 (Al-Quoz)  
Fax : +971 4 347 1713  
Tel : +971 4 880 1212 (Jebel Ali)  
Fax : +971 4 880 1033  
Email: info.dubai@cemex.com

**Dubai**

Cement & Slag (GGBS)  
CEMEX FALCON LLC  
PO Box 66429  
Jebel Ali Industrial Area  
Dubai, UAE  
Tel : +971 4 880 1212  
Fax : +971 4 880 1033

**Abu Dhabi**

Ready-Mix Concrete  
CEMEX SUPERMIX LLC  
PO Box 72071  
Mussafah Industrial Area  
Abu Dhabi, UAE  
Tel : +971 2 551 5501  
Fax : +971 2 551 5560  
Email: info.abudhabi@cemex.com

| [www.cemex.ae](http://www.cemex.ae) |

Copyright © 2015 CEMEX Research Group, AG



**DECORATIVE PAVING**



Building the future™

# DECORATIVE PAVING



## What is Decorative Concrete?

Decorative concrete by CEMEX is a range of products with different surface finishes to provide a modern, economic, robust and visually appealing finish for paved areas.

## Why Decorative Concrete?

Decorative concrete is many times stronger than traditional paving solutions such as asphalt and interlock paving which often deform under loading or adverse weather conditions, resulting in unsightly uneven surfaces which need repairing and replacing.

Decorative concrete is low maintenance, with routine cleaning of the surface being sufficient to maintain its appearance.

Decorative concrete can provide a wide variety of finishes and colours to match the requirement of development.



**CX DECORATIVE PAVING** is an efficient and very cost-effective solution that can be engineered to suit your project needs. Decorative pavement can be design to compliment your unique style into your interior and exterior areas. We offer Supply and Apply solutions that are tailor made project by project and carefully executed by certified applicator.

### SUITABLE FOR:

- Patios
- Swimming Pool Area
- Path ways
- Drive ways and parking areas
- Landscaping and green areas

### ADVANTAGES:

- High durability with low maintenance cost.
- Variety of colors and texture
- Warranty applicable
- The usage of supplementary cementitious material is possible hence compliance with DM Circular 202 & Estdidama

Bring colour to your outdoor living space



## PERFORMANCE FOOTPRINT



## TECHNICAL DATA

Flexural Grade(N/mm <sup>2</sup> )	3.0 to 6.0
Slump (mm)	30 to 150
Slump Retention (min)	45 to 120
Maximum Aggregate (mm)	20 – 40
Typical Density (Kg/m <sup>3</sup> )	2,400
Cement Type	OPC, SRC, MSRCP
Supplementary Cements	GGBS, Microsilica, PFA